

## LED Strip Light



## Specifications

Model No.	SLWW-12V-10M
LED Density	60 pcs/m
Cuttable Segments	3 LEDs 50mm (12V DC) 6 LEDs 100mm (24V DC)
PCB Type/Color	2 oz , White PCB
Dimension:	10000*8mm
Max Run Length	5 m
Package	10 m/bag

Input Voltage	12V DC 24V DC
Peak Power (w/m)	5 w/m
Lumen (Lm/m)	440-470Lm/m
Ra	Ra>92
IP Grade	IP20/IP54/IP65/IP67/IP68
Warranty	5 Years
Certification	UL CE RoHS

## Typical Color

Color	CCT Wavelength
6000K	
5000K	
4000K	
3500K	
3000K	
2700K	
2500K	
2300K	
2100K	
1900K	
R/G/B/P/V/Y	

## Lumen Count

Color	Per Meter
6000K	
5000K	
4000K	
3500K	
3000K	
2700K	
2500K	
2300K	
2100K	
1900K	
R/G/B/P/V/Y	

NOTES: More customized colors, please contact our sales .

## Packing Information

**Standard Packing Per Bag**  
5 meters/reel, 1 reel/anti-static bag  
G.W. : Non-waterproof-0.20KG

**Standard Packing Per Outer Carton**  
25 bags to 1 inner box, size : 33.5x20x24cm  
4 inner boxes to 1 outer carton size: 42x35x46cm  
G.W of Carton: 10.8 kg  
Volume of Carton: 0.068 m<sup>3</sup>

## NOTES

1. STERLING LED LIGHTING LED Strip maintains a tester tolerance of  $\pm 5\%$  on Color Temperature and Lumen , tolerance of  $\pm 3$  on CRI-Ra
2. The test is based on the STERLING LED LIGHTING's laboratory and testing equipment.
3. We reserve the right to modify and improve the design of our fixtures without prior notice.

## LED Strip Light



## Specifications

Model No.	SLCW-12V-25M
LED Density	60 pcs/m
Cuttable Segments	3 LEDs 50mm (12V DC) 6 LEDs 100mm (24V DC)
PCB Type/Color	2 oz , White PCB
Dimension:	25000*8mm
Max Run Length	5 m
Package	25 m/bag

Input Voltage	12V DC 24V DC
Peak Power (w/m)	5 w/m
Lumen (Lm/m)	440-470Lm/m
Ra	Ra>92
IP Grade	IP20/IP54/IP65/IP67/IP68
Warranty	5 Years
Certification	UL CE RoHS

## Typical Color

Color	CCT Wavelength
6000K	
5000K	
4000K	
3500K	
3000K	
2700K	
2500K	
2300K	
2100K	
1900K	
R/G/B/P/V/Y	

## Lumen Count

Color	Per Meter
6000K	
5000K	
4000K	
3500K	
3000K	
2700K	
2500K	
2300K	
2100K	
1900K	
R/G/B/P/V/Y	

NOTES: More customized colors, please contact our sales .

## Packing Information

### Standard Packing Per Bag

5 meters/reel,1 reel/anti-static bag  
G.W. : Non-waterproof-0.20KG

### Standard Packing Per Outer Carton

25 bags to 1 inner box, size : 33.5x20x24cm  
4 inner boxes to 1 outer carton size: 42x35x46cm  
G.W of Carton: 10.8 kg  
Volume of Carton: 0.068 m<sup>3</sup>

## NOTES

1. STERLING LED LIGHTING LED Strip maintains a tester tolerance of  $\pm 5\%$  on Color Temperature and Lumen , tolerance of  $\pm 3$  on CRI-Ra
2. The test is based on the STERLING LED LIGHTING's laboratory and testing equipment.
3. We reserve the right to modify and improve the design of our fixtures without prior notice.